

Property/Standard	Description	Unit	Value / Result
Overall Thickness	2.5 mm solid vinyl tile and plank	Millimeter / Inch	2.5 / 0.098
Wearlayer Thickness	20.0 mil	Millimeter / Inch	0.5 / 0.020
Urethane	Ceramglaz™ Polyurethane Coating		Yes
Plank Size		Millimeter / Inch	152.4 x 609.6, 177.8 x 1219.2 6 x 24, 7 x 48
Tile Size		Millimeter / Inch	604.8 x 609.6mm / 12 x 24
Edge Effect			MicroBevel
Floor Score			Yes
Residential Warranty	Limited Wear / Mechanical		Lifetime / 1 year
Commercial Warranty	Limited Wear / Mechanical		10 Years / 1 year
Number of Patterns	6" x 24" plank		4 SKUs
	7" x 48" plank		10 SKUs
	12" x 24" tile		4 SKUs
Packaging	6" x 24" plank	ft ² /Pcs./Ctn. plt	32 ft ² / 32 Pcs. / 60 Ctn.
	7" x 48" plank		35 ft ² / 15 Pcs. / 55 Ctn.
	12" x 24" tile		36 ft ² / 18 Pcs. / 54 Ctn.
Package weight	6" x 24" plank	Lbs.	29.1
	7" x 48" plank		31.75
	12" x 24" tile		32.63
ASTM F1700-13	Solid Vinyl Floor Tile		Class III, Type B
ASTM F137-08	Flexibility		Passes
ASTM F386-11	Thickness		Passes
ASTM F925	Stain and Chemical resistance		Excellent
ASTM F1514	Heat Stability		Excellent
ASTM F1515	Light Stability		Excellent
ASTM F1914	Immediate & Residual Indentation		Passes
ASTM 2055	Size and Squareness		Passes
ASTM F2199-09	Dimensional Stability		Passes
ASTM D2047	Static COF for Polished Surfaces		Exceeds
ASTM E648-06	Critical Radiant Flux		Class 1
ASTM E662	Smoke Density		<450 sdi/Passes
Static Load Limit	Modified test procedure		> 1,200 psi